

PRODUCT GUIDE AND SPECIFICATIONS

KX-TDE100 KX-TDE200

PGMPR SOFTWARE FILE VERSION 5.0



SYSTEM CAPACITY			
MAXIMUM TRUNKS AND EXTENSIONS The PBX supports the following number of trunks and extensions			
TYPE	KX-TDE100	KX-TDE200	
TOTAL NUMBER OF TRUNKS			
Trunk (Physical Trunk Card)	120	128	
Trunk (Virtual Trunk Card)	64	64	
	H.323 Trunks	32	32
	SIP Trunks	64	64
TOTAL NUMBER OF EXTENSIONS			
Extension (Physical Extension Card)	256	256	
Extension (Virtual Extension Card)	160	256	
	IP-PT and IP Softphone	128	128
	SIP Extension	128	128

MAXIMUM TERMINAL EQUIPMENT			
The following shows the number of each terminal equipment type supported by the PBX			
TERMINAL EQUIPMENT TYPE	KX-TDE100	KX-TDE200	
TELEPHONE			
SLT	256	256	
KX-DT300/KX-T7600 series DPT	128	168	
Other DPT	128	256	
APT	32	128	
IP-PT	24	64	
	192	192	
	IP-PT ¹⁾ (supported by IP-EXT16 card)	96	128
	IP-PT ²⁾ (supported by IPCEMPR card)	128 ³⁾	128 ³⁾
SIP Extension	128	128	
DSS CONSOLE			
CS	8	8	
	32 ⁴⁾	32 ⁴⁾	
	PT-interface CS (2-channel) /CS for CSIF card	32	32
	PT-interface CS (8-channel)	16	16
	IP-CS (8-channel)	16	16
PS			
Voice Processing System (VPS) ⁵⁾	128	128	
Doorphone	2	2	
Door Opener	16	16	
External Sensor	16	16	
External Relay	16	16	

¹⁾ KX-NT300 series (except KX-NT366/KX-NT305), KX-NT265, and KX-NT136

²⁾ KX-NT400, KX-NT300 series and KX-NT265 (software version 2.00 or later only)

³⁾ For the KX-NT400, the maximum number of extensions that can be connected to the PBX is 64.

⁴⁾ One 8-channel PT-interface CS or IP-CS counts as 2 CSs for the total number of CSs.

OPTION LIST	Model	Description
IPCMR OPTIONAL CARDS		
	KX-TDE0105	Memory Expansion Card (IPCEC)
	KX-TDE0101	IP Convergence Main Processing Card(IPCEMPR)
	KX-TDE0110	16-Channel VoIP DSP Card
	KX-TDE0111	64-Channel VoIP DSP Card
	KX-TDA0196	Remote Card
ACTIVATION KEY CODES¹⁾		
	KX-NCS4102	2-Channel IP Trunk Activation Key
	KX-NCS4104	4-Channel IP Trunk Activation Key
	KX-NCS4201	1-Channel IP Softphone/IP Proprietary Telephone Activation Key
	KX-NCS4204	4-Channel IP Softphone/IP Proprietary Telephone Activation Key
	KX-NCS4208	8-Channel IP Softphone/IP Proprietary Telephone Activation Key
	KX-NCS4216	16-Channel IP Softphone/IP Proprietary Telephone Activation Key
	KX-NCS4501	1-Channel IP Proprietary Telephone Activation Key
	KX-NCS4504	4-Channel IP Proprietary Telephone Activation Key
	KX-NCS4508	8-Channel IP Proprietary Telephone Activation Key
	KX-NCS4516	16-Channel IP Proprietary Telephone Activation Key
	KX-NCS4701	1-Channel SIP Extension Activation Key
	KX-NCS4704	4-Channel SIP Extension Activation Key
	KX-NCS4708	8-Channel SIP Extension Activation Key
	KX-NCS4716	16-Channel SIP Extension Activation Key
	KX-NCS4910	Activation Key for Enhanced Features
	KX-NCS2010	Activation Key for CA Thin Client
	KX-NCS2020	Activation Key for CSTA Multiplexer
	KX-NCS2201	Activation Key for CA PRO for 1 User
	KX-NCS2205	Activation Key for CA PRO for 5 Users
	KX-NCS2210	Activation Key for CA PRO for 10 Users
	KX-NCS2240	Activation Key for CA PRO for 40 Users
	KX-NCS2249	Activation Key for CA PRO for 128 Users
	KX-NCS2301	Activation Key for CA ACD Monitor for 1 ICD Supervisor
	KX-NCS2401	Activation Key for CA Operator Console 1 User
	KX-NCS2901	Activation Key for CA Network 1 User
	KX-NCS2905	Activation Key for CA Network 5 Users
	KX-NCS2910	Activation Key for CA Network 10 Users
	KX-NCS2940	Activation Key for CA Network 40 Users
	KX-NCS2949	Activation Key for CA Network 128 Users
	KX-NCS3930	Activation Key for Third Party CTI
PHYSICAL TRUNK CARDS		
	KX-TDA0180	8-Port Analogue Trunk Card (LC0T8)
	KX-TDA0181	16-Port Analogue Trunk Card (LC0T16)
	KX-TDA0182	8-Port DID Card (DID8)
	KX-TDA0184	8-Port E & M Trunk Card (E&M8)
	KX-TDA0188	E-1 Trunk Card (E1)
	KX-TDA0189	8-Port Caller ID/Pay Tone Card (CID/PAY8)
	KX-TDA0193	8-Port Caller ID Card (CID8)
	KX-TDA0284	4-Port BRI Card (BRI4)
	KX-TDA0288	8-Port BRI Card (BRI8)
	KX-TDA0290	PRI Card
	KX-TDA0484	4-Channel VoIP Gateway Card (IP-GW4E)
	KX-TDA0490	16-Channel VoIP Gateway Card (IP-GW16)
PHYSICAL EXTENSION CARDS		
	KX-TDA0143	4 Cell Station Interface Card (CSIF4)
	KX-TDA0144	8 Cell Station Interface Card (CSIF8)
	KX-TDA0170	8-Port Digital Hybrid Extension Card (DHLHC8)
	KX-TDA0171	8-Port Digital Extension Card (DLC8)
	KX-TDA0172	16-Port Digital Extension Card (DLC16)
	KX-TDA0173	8-Port Single Line Telephone Extension Card (SLC8)
	KX-TDA0174	16-Port Single Line Telephone Extension Card (SLC16)
	KX-TDA0175	16-Port Single Line Telephone Extension with Message Lamp Card (MSLC16)
	KX-TDA0177	16-Port Single Line Telephone Extension Card with Caller ID (CSLC16)
	KX-TDA0470	16-Channel VoIP Extension Card (IP-EXT16)
	KX-TDA1176	16-Port Single Line Telephone Extension with Caller ID and Message Lamp Card (MCSLC16)
	KX-TDA1178	24-Port Single Line Telephone Extension with Caller ID and Message Lamp Card (MCSLC24)
OTHER PHYSICAL CARDS		
	KX-TDA0161	4-Port Doorphone Card (DPH4)
	KX-TDA0162	2-Port Doorphone Card (German Type) (DPH2)
	KX-TDA0164	4-Port External Input/Output Card (EI04)
	KX-TDA0166	16-Channel Echo Canceller Card (ECH016)
	KX-TDA0168	Extension Caller ID Card (EXT-CID)
	KX-TDA0190	Optional 3-Slot Base Card (OPB3)
	KX-TDA0191	4-Channel Message Card (MSG4)
	KX-TDA0192	2-Channel Simplified Voice Message Card (ESVM2)
	KX-TDA0194	4-Channel Simplified Voice Message Card (ESVM4)
POWER SUPPLY UNITS (PSUS)		
	KX-TDA0103	L-Type Power Supply Unit (PSU-L)
	KX-TDA0104	M-Type Power Supply Unit (PSU-M)
	KX-TDA0108	S-Type Power Supply Unit (PSU-S)
CELL STATION (CSS) DECT		
	KX-TDA0155	2-Channel Cell Station Unit Using a DHLHC/DLC Card (PT-interface CS) for DECT Portable Station
	KX-TDA0156	4-Channel Cell Station Unit Using a CSIF Card for DECT Portable Station
	KX-TDA0158	8-Channel High-density Cell Station Unit Using a DHLHC/DLC Card (PT-interface CS) for DECT Portable Station
	KX-NCP0158	8-Channel IP Cell Station Unit Using a V-IPCS4 Card for DECT Portable Station
PROPRIETARY EQUIPMENT		
	KX-A228	S/M-type Back-up Battery Cable
	KX-A229	L-type Back-up Battery Cable
	KX-A258	Blank Slot Cover
	KX-T30865	Doorphone
	KX-T7765	Doorphone

¹⁾ Note that the types of activation keys are subject to change without notice. For CA activation keys, refer to the documentation for CA.

Compatible Panasonic Proprietary Telephones

The PBX supports the following telephones:

- IP proprietary telephones (e.g., KX-NT300 series) - IP softphones (e.g., KX-NCS8100) - Digital proprietary telephones (e.g., KX-DT300 series)
- Analogue proprietary telephones (e.g., KX-T7700 series)
- Portable stations (e.g., KX-WT115, KX-TCA355, KX-TCA275) - DSS consoles (e.g., KX-DT390) - Single line telephones (e.g., KX-T7710)

Incompatible Panasonic Proprietary Telephones

The PBX does not support the following telephones:

- KX-T30800 series proprietary telephones and DSS consoles - KX-T61600 series proprietary telephones and DSS consoles
- KX-T123200 series proprietary telephones and DSS consoles - KX-TD7500 DECT portable station

Note: Some models will be exported to limited region. Please contact our dealer and confirm the availability of specific models in your region.

SYSTEM FEATURE CAPACITY			
	Item	KX-TDE100	KX-TDE200
SYSTEM	Absent Message—Extension	1 x 16 characters	
	Absent Message—System	8 x 16 characters	
	Call Park Zone	100	
	Conference	3-8 parties per conference (32 parties total)	
	COS	64	
	DID/DDI Table	32 digits, 1000 entries	
	Extension number	1 - 5 digits	
	Extension Personal Identification Number (PIN)	10 digits, 1 entry/extension	
	Host PBX Access Code	10 digits, 10 entries/trunk group	
	Multiple Subscriber Number (MSN)	10 entries per ISDN-BRI port	
	Number of Characters of Name	20	
	Printing message	8	
	Queuing Time Table	64	
	Ring Tone Pattern Plan	8	
	Simultaneous Programmers	- one system programmer + 63 personal programmers - one manager programmer + 63 personal programmers	
	SMDR Call Storage	- 64 personal programmers 200 calls (10 000 calls w/ IPCMEC card)	
	Special Carrier Access Code	16 digits, 20 entries	
Tenant	8		
Time Service Holiday	24		
Verification Code	4 digits, 1000 entries		
Verification Code Personal Identification Number (PIN)	10 digits, 1000 entries		
DIALLING	Emergency Call	32 digits, 10 entries	
	Hot Line	32 digits	
	Key Pad Protocol Dial (ISDN Service Access)	32 digits	
	Personal Speed Dialling	32 digits, 100 entries/extn.	
	Quick Dialling	8 digits, 4080 entries	
	Redial	32 digits	
	System Speed Dialling	32 digits, 1000 entries/tenant	
	One-touch Dialling—PT/DSS	32 digits, 2000 entries/system	
	One-touch Dialling—PS	32 digits, 500 entries/system	
	GROUPS	Conference Group	8 (8 members/group for Conference Group Mode, 32 members/group for Broadcast Mode)
Call Pickup Group		64	
Idle Extension Hunting Group		64 (16 extensions/group)	
Incoming Call Distribution Group		128 (128 extensions/group)	
Paging Group		32	
PS Ring Group		32	
Trunk Group		64	
VM (DPT) Group		2 groups x 12 ports (24 channels)	
VM (DTMF) Group		2 groups x 32 channels	
TRS/BARRING		TRS/Barring Level	7
	TRS/Barring Denied Code	16 digits, 100 entries/level	
	TRS/Barring Exception Code	16 digits, 100 entries/level	
ARS	Routing Plan Table	16 entries	
	Leading Number Table	16 digits, 1000 entries	
	Leading Number Exception Table	16 digits, 200 entries	
	ARS Carrier	10	
	Itemised Billing Code	10 digits	
	Authorisation Code for Tenant	16 digits	
CALL LOG AND MESSAGE WAITING	Authorisation Code for Trunk Group	10 digits	
	Outgoing Call Log—PT	100 records/extn. 1520 records/system	
	Outgoing Call Log—PS	100 records/extn. 640 records/system	
	Incoming Call Log—PT	100 records/extn. 3040 records/system	
	Incoming Call Log—PS + Incoming Call Distribution Group	100 records/extn. or group Total 2048 records/system	
	Message Waiting—PS + Incoming Call Distribution Group	256	
VOICE MESSAGE	Message Waiting—PT + SLT	512	
	Outgoing Message (OGM)	64	
	OGM Total Recording Time	MSS4 Card: 8 minutes; MPR/ESVM2/ESVM4 Card: 20 minutes (at High recording quality)	
	Built-in Simplified Voice Message (SVM)	MPR Card: 125 messages; ESVM2/ESVM4 Card: 250 messages per card/block	
HOSPITALITY AND CHARGE MANAGEMENT FEATURES	SVM Total Recording Time	20, 60, or 120 minutes (depending on the recording quality)	
	Billing items for guest rooms	4000 records/PBX	
	Hotel Operator	4	
	Charge Rate	7 digits including a decimal	
NETWORKING	Charge Denomination	3 currency characters/symbols	
	TIE Line Routing and Modification Table	32 entries	
	Leading Number	3 digits	
	PBX Code	7 digits	
	NDS: Monitored PBXs	8	
	NDS: Registered Extensions for Monitor PBX	250	
CTI	PC Console	8	8
	PC Phone	64	128
PASSWORD	System Password for Installer	4 - 10 characters	
	System Password for Administrator—for PC Programming	4 - 10 characters	
	System Password for User—for PC Programming	4 - 10 characters	
	System Password for Administrator—for PT Programming	4 - 10 digits	
	System Password for User—for PT Programming	4 - 10 digits	
	Manager Password	4 - 10 digits	
PROGRAMMER CODE	Installer Level Programmer Code	4 - 16 characters	
	Administrator Level Programmer Code	4 - 16 characters	
	User Level Programmer Code	0 - 16 characters	



SPECIFICATIONS		KX-TDE100	KX-TDE200
Control Bus		Original bus (16-bit, 8 MHz, 10 megabytes per second)	
Communication Bus		H.100 bus conformity (1024 time slots)	
Switching		Non-blocking	
POWER INPUT	PSU-S	100 V AC to 130 V AC; 1.4 A/200 V AC to 240 V AC; 0.8 A (50 Hz/60 Hz)	
	PSU-M	100 V AC to 130 V AC; 2.5 A/200 V AC to 240 V AC; 1.4 A (50 Hz/60 Hz)	
	PSU-L	100 V AC to 130 V AC; 5.1 A/200 V AC to 240 V AC; 2.55 A (50 Hz/60 Hz)	
External Battery		+36 V DC (+12 V DC x 3, recommended maximum capacity is 28 Ah)	
Maximum Power Failure Tolerance		300 ms (without using backup batteries)	
Memory Backup Duration		7 years	
DIALLING	Trunk	Dial Pulse (DP) 10 pps, 20 pps Tone (DTMF) Dialling	
	Extension	Dial Pulse (DP) 10 pps, 20 pps Tone (DTMF) Dialling	
Mode Conversion		DP-DTMF, DTMF-DP	
Ring Frequency		20 Hz/25 Hz (selectable)	
Trunk Loop Limit		1600 Ω maximum	
OPERATING ENVIRONMENT	Temperature	0 °C to 40 °C	
	Humidity	10 % to 90 % (non-condensing)	
Conference Call Trunk		300 ms (without using backup batteries)	
Music on Hold (MOH)		2 ports (Level Control: -11dB to +11dB in 1dB steps). [MOH1] External Music Source port. [MOH2] Selectable. Internal/External Music Source port.	
PAGING	Internal	Level Control: -15 dB to +6 dB in 3 dB steps	
	External	2 ports (Volume Control: -15 dB to +15 dB in 1 dB steps)	
Serial Interface Port	RS-232C	1 (maximum 115.2 kbps)	
RJ45 PORT	MNT Port	1 (for PC connection)	
	LAN Port	1 (for LAN connection)	
Extension Connection Cable	SLT	1-pair wire (T, R)	
	DPT	1-pair wire (D1, D2) or 2-pair wire (T, R, D1, D2)	
	APT	2-pair wire (T, R, D1, D2)	
	PT-interface CS (2-channel)	1-pair wire (D1, D2)	
	PT-interface CS (8-channel)	4-pair wire (D1, D2)	
DSS Console and Add-on Key Module		1-pair wire (D1, D2)	
DIMENSION	KX-TDE100	334 mm(W) x 390 mm (H) x 272 mm (D)	
	KX-TDE200	430 mm (W) x 415 mm (H) x 276 mm (D)	
Weight (when fully mounted)	KX-TDE100	Under 12 kg	
	KX-TDE200	Under 16 kg	

02122011.01.UK

OneNet



Panasonic ideas for life

We expressly reserve the right to make reasonable changes to models, dimensions, colours as well as to make modifications that bring our products in line with state-of-the-art technology.